

hpdSYSTEM vario

- ✓ HOT FOIL CODING SYSTEM WITH CASSETTE
- ✓ FOR INDIVIDUAL PRODUCT CODING
- ✓ UP TO 1.000 PRINTS/MIN.



Simple. Runs. Always.

INKJET Thermal Transfer Overprint

HOTFOIL-CODING **LASER** *Thermal-Inkjet* *Offline coding*

For use-by-dates **AFTER SALES** **BARCODE** *etc.*

CODING SYSTEMS

„MADE IN GERMANY“

Print

- up to 30 x 50 mm printing format
- 1000 prints / min.
- Print time:: 20 x 2000 ms
- Temperature: 50 – 220 ° C
- Printing pressure: 580 N at 6 bar

Film

- Colour foil length: 305 m
- Foil diameter: 100 mm
- Film feed 2 – 30 mm infinitely variable
- Displays film end
- Printer reset function

Printing accessories

- PC-software hpdCONTROL
- Types, counters
- Standard-mounting frame



Control unit

- 24 V / 10 A: with graphical display and keypad, interface RS 232, for second printer connection suitable, IP 54
- 110 - 240 V / 1 - 2 A: with graphical display and keypad, interface RS 232, IP 54
- Powerbox 110 - 240 V / 1 - 2 A









Technical data

Dimensions vertical:	206 x 190 x 166 mm, H x W x T
Installation height:	206 mm
Dimensions horizontal:	142 x 285 x 166 mm, H x W x T
Installation height:	142 mm
Weight:	6,5 kg
Drive type:	pneumatic drive
Air connection:	min. 4 – max. 6 bar, ø 6 mm

Compressed air consumption:	ca. 0,16 l per printing cycle
Power requirements:	24 V DC ± 10 %, 125 VA
Protection class:	Printer: IP 20
Temperature:	323 - 473 K (50° - 200° C) (infinitely variable)
Heating power:	120 W

Type

- vertikal, optionally
 - right device variant
 - left device variant
- horizontal, optionally
 - right device variant
 - left device variant



Subject to technical and design changes.
E&OE